



1560 Lisbon Street, Lewiston, Maine 04240
 Telephone: 207-333-6100 • Toll Free: 800-343-8008 (USA)
 www.elmettechnologies.com

Certified to ISO 9001 & 14001

Standard Coiled Coils for Incandescent Lamps

Part Number	Power Watts	Driver Volts	Life Hours	Design Lms/W	Lamp Type	Shape	Total Lgth [MM]	End Lgth [MM]
323558828500	25	120	1000	10.5	A19	CC6	20	4.8
323556164400	25	120	2000	9.3	G25	CC6	20	4.8
323551598400	25	120	2500	9.7	A19	CC6	20	4.8
323554059900	25	120	3350	9.3	A19	CC6	20	4.8
323553871400	25	125	1000	10.4	A19	CC6	20	4.8
323556746000	25	125	2500	10.0	A19	CC6	20	4.8
323556164000	25	130	2000	9.2	G25	CC6	20	4.8
323551598600	25	130	2500	9.4	A19	CC6	20	4.8
323555677100	34	120	1500	11.7	A19	CC6	20	4.0
323555688800	34	125	2500	10.5	A19	CC6	20	4.0
323555677200	34	130	1500	11.4	A19	CC6	20	4.0
323558363300	40	120	1000	13.0	A19	CC6	20	2.5
323551162700	40	120	1250	11.6	A19	CC6	20	2.5
323558021700	40	120	1500	11.7	A19	CC6	20	2.5
323555958200	40	120	1700	11.7	A19	CC6	20	2.5
323555079200	40	120	2000	11.5	A19	CC6	20	2.5
323556164100	40	120	2000	10.7	G25	CC6	20	2.5
323553871300	40	125	1000	12.8	A19	CC6	20	2.5
323555677000	40	125	1500	12.2	A19	CC6	20	2.5
323555674900	40	125	2500	11.0	A19	CC6	20	2.5
323558022500	40	130	1500	12.1	A19	CC6	20	2.5
323556164200	40	130	2000	11.3	G25	CC6	20	2.5
323551449500	40	130	2500	11.2	A19	CC6	20	2.5
323554329000	50	120	1000	13.5	A19	CC6	20	2.5
323553254800	50	120	2000	9.9	RM19	CC6	22	3.0
323556753300	50	120	2500	7.7	R20	CC6	22	3.0
323554951700	50	125	2000	10.6	ER30	CC6	22	2.5
323551157600	60	120	1000	14.1	A19	CC6	20	2.5
323555072000	60	120	1250	13.9	A19	CC6	20	2.5
323551162900	60	120	1350	13.9	A19	CC6	20	2.5
323556893000	60	120	1500	13.7	A19	CC6	20	2.5
323555958100	60	120	1700	12.9	A19	CC6	20	2.5
323556164300	60	120	2000	12.0	G25	CC6	20	2.5
323558581000	60	120	2500	13.0	A19	CC6	20	2.5
323553073800	60	125	1000	14.4	A19	CC6	20	2.5
323556803100	60	125	2000	12.8	G25	CC6	20	2.5
323558582800	60	125	2500	12.9	A19	CC6	20	2.5
323557727000	60	130	1000	14.4	A19	CC6	20	2.5
323558584400	60	130	2500	12.3	A19	CC6	20	2.5
323551158400	75	120	750	16.0	A19	CC6	23	2.5
323551157100	75	120	1000	15.3	A19	CC6	23	2.5



1560 Lisbon Street, Lewiston, Maine 04240
 Telephone: 207-333-6100 • Toll Free: 800-343-8008 (USA)
 www.elmettechnologies.com

Certified to ISO 9001 & 14001

Standard Coiled Coils for Incandescent Lamps

Part Number	Power Watts	Driver Volts	Life Hours	Design Lms/W	Lamp Type	Shape	Total Lgth [MM]	End Lgth [MM]
323555079000	75	120	1500	13.7	A19	CC6	23	2.5
323555958000	75	120	1700	14.2	A19	CC6	23	2.5
323554420800	75	120	2000	8.8	R30	CC6	24	2.5
323557505500	75	120	2000	12.8	A19	CC6	21	4.0
323556829700	75	120	2500	8.5	R20	CC6	24	2.5
323553871200	75	125	1000	15.2	A19	CC6	23	2.5
323555802500	75	125	2000	9.4	BR30	CC6	22	2.5
323555651000	75	125	2500	13.1	A19	CC6	23	2.5
323555091100	75	125	5000	10.5	BR30	CC6	22	2.5
323557726200	75	130	750	15.7	A19	CC6	23	2.5
323554477200	75	130	1000	15.0	A19	CC6	23	2.5
323557505600	75	130	2000	12.5	A19	CC6	21	3.8
323554420900	75	130	2000	8.5	R30	CC6	24	2.5
323550713300	100	120	750	16.3	A19	CC6	23	2.5
323558530700	100	120	1000	15.6	A19	CC6	23	2.5
323551165600	100	120	1350	15.0	A19	CC6	23	2.5
323555079100	100	120	1500	14.7	A19	CC6	23	2.5
323555958400	100	120	1700	15.5	A19	CC6	23	2.5
323556649600	100	120	2000	14.1	A19	CC6	23	2.5
323550718200	100	120	2500	14.2	A19	CC6	23	2.5
323553871100	100	125	1000	15.5	A19	CC6	23	2.5
323556802800	100	125	2000	14.0	A19	CC6	23	2.5
323555091000	100	125	5000	11.4	BR40	CC6	26	2.5
323551002100	100	130	750	15.9	A19	CC6	23	2.5
323558823600	100	130	1000	15.3	A19	CC6	23	2.5
323551164800	100	130	2500	14.0	A19	CC6	23	2.5
323555181500	120	120	2000	10.6	BR40	CC6	24	2.5
323575582700	120	120	2000	12.8	BR40	CC6	28	4.0
323555191400	120	120	2500	10.1	BR40	CC6	22	2.5
323555179100	120	125	2000	10.4	BR40	CC6	24	2.5
323555703800	120	125	5000	9.6	BR40	CC6	22	2.5
323555179000	120	130	2000	10.3	BR40	CC6	24	2.5
323557505400	120	130	2000	11.5	ER40	CC6	24	4.5
323575589200	120	130	2000	12.5	BR40	CC6	28	4.0
323568965300	150	120	2000	11.8	R40	CC6	28	4.0
323557497900	40	120	1650	12.4	A19	CC8	21	4.4
320040002500	40	120	3000	9.8	A19	CC8	21	4.1
323557498000	50	120	1200	12.7	A21	CC8	21	3.9
323556971200	60	120	1500	13.7	A19	CC8	24	3.0
323557498100	60	120	2000	13.1	A19	CC8	28	4.8
323554188100	75	130	1000	15.9	A21	CC8	32	5.0



1560 Lisbon Street, Lewiston, Maine 04240
 Telephone: 207-333-6100 • Toll Free: 800-343-8008 (USA)
 www.elmettechnologies.com

Certified to ISO 9001 & 14001

Standard Coiled Coils for Incandescent Lamps

Part Number	Power Watts	Driver Volts	Life Hours	Design Lms/W	Lamp Type	Shape	Total Lgth [MM]	End Lgth [MM]
323553970600	100	120	750	17.0	A21	CC8	33	5.0
323565739500	100	120	750	17.4	A19	CC8	24	3.0
323550301100	100	120	1200	16.1	A19	CC8	31	5.5
323557497800	100	120	1200	14.8	A21	CC8	31	3.6
323557367000	100	120	1400	16.0	A19	CC8	24	3.0
323550795400	100	120	1500	15.2	A19	CC8	24	3.0
323554961300	100	120	1500	15.6	A19	CC8	31	5.5
323556840100	100	120	1750	14.1	A19	CC8	31	5.5
320040012500	100	120	3000	16.0	T3	CC8	24	4.0
323555665500	100	125	750	16.9	A21	CC8	33	5.0
323554942700	100	125	2500	14.2	A21	CC8	31	5.5
323554560400	100	130	3500	13.4	A21	CC8	31	5.5
320040002400	150	120	750	19.0	A21	CC8	32	3.5
323568904200	150	120	750	18.9	A21	CC8	32	5.0
323555386900	150	120	1000	19.0	A19	CC8	33	5.0
323556649500	150	120	2000	17.1	A23	CC8	33	5.0
323568905900	150	125	750	18.8	A21	CC8	32	5.0
323554943000	150	125	2500	16.3	A21	CC8	32	5.0
323578771300	150	130	750	18.9	A23	CC8	33	5.0
323555386400	150	130	2500	16.2	A21	CC8	33	5.0
323569022200	200	120	750	20.0	A23	CC8	33	5.0
323569025500	200	120	1000	19.2	T21	CC8	33	5.0
323556840300	200	120	1750	16.6	T21	CC8	32	5.0
323569023000	200	125	750	19.8	A23	CC8	33	5.0
323555651500	200	125	2500	17.3	A23	CC8	33	5.0
323569024800	200	130	750	19.7	A23	CC8	33	5.0
323550105600	200	130	2500	17.2	A23	CC8	33	5.0
323554298300	75	140	1000	14.3	A60	CC6	27	2.0
323557527300	75	230	3500	10.7	A60	CC9	35	3.3
323557115900	80	230	2000	10.1	PAR38	CC9	31	3.9
323557116000	80	240	2000	9.9	PAR38	CC9	31	3.9
323555191000	84	120	2000	10.4	BR30	CC6	22	3.0
323555179200	84	130	2000	10.1	BR30	CC6	22	3.0
323555336400	85	120	2500	9.7	BR30	CC6	22	3.0
323557505700	85	130	3000	9.8	BR40	CC6	21	4.9
323556605100	90	110	2500	18.7	T4	CC8	20	4.0
323555688500	90	120	750	16.2	A19	CC6	23	2.5
323557520500	90	120	1500	15.6	A19	CC6	23	3.6
323555090300	90	120	2000	19.0	T4	CC8	17	2.7
323555422200	90	120	2500	18.4	T4	CC8	20	4.0
323556637600	90	120	2500	18.4	T4	CC8	20	4.0
323556652900	90	120	3000	17.8	T4	CC8	20	4.0
323557522900	90	125	1500	15.4	A19	CC6	23	3.6



1560 Lisbon Street, Lewiston, Maine 04240
 Telephone: 207-333-6100 • Toll Free: 800-343-8008 (USA)
 www.elmettechnologies.com

Certified to ISO 9001 & 14001

Standard Coiled Coils for Incandescent Lamps

Part Number	Power Watts	Driver Volts	Life Hours	Design Lms/W	Lamp Type	Shape	Total Lgth [MM]	End Lgth [MM]
323555688700	90	125	2500	13.5	A19	CC6	23	2.5
323555688400	90	130	750	15.9	A19	CC6	23	2.5
323555340600	90	130	2000	18.9	T4	CC8	17	2.7
323555422300	90	130	2500	17.9	T4	CC8	20	4.0
323556609400	90	130	2500	17.9	T4	CC8	20	4.0
323554174400	92	120	1000	15.6	A19	CC6	23	2.5
323556959900	98	120	3000	18.4	T4	CC8	21	4.0
323554107200	100	117.5	1000	15.7	A19	CC6	23	2.5
323553970600	100	120	750	17.0	A21	CC8	33	5.0
323565739500	100	120	750	17.4	A19	CC8	24	4.1
323550713300	100	120	750	16.3	A19	CC6	23	2.5
323558530700	100	120	1000	15.6	A19	CC6	23	3.6
323557497800	100	120	1200	14.8	A21	CC8	31	4.7
323550301100	100	120	1200	16.1	A19	CC8	31	5.5
323551165600	100	120	1350	15.0	A19	CC6	23	2.5
323557367000	100	120	1400	16.0	A19	CC8	24	4.1
323554961300	100	120	1500	15.6	A19	CC8	31	5.5
323555079100	100	120	1500	14.7	A19	CC6	23	2.5
323550795400	100	120	1500	15.2	A19	CC8	24	4.1
323555958400	100	120	1700	15.5	A19	CC6	23	2.5
323556840100	100	120	1750	14.1	A19	CC8	31	5.5
323556649600	100	120	2000	14.1	A19	CC6	23	2.5
323556711900	100	120	2500	20.0	T4	CC8	23	4.0
323556637800	100	120	2500	18.8	T4	CC8	23	4.0
323550718200	100	120	2500	14.2	A19	CC6	23	2.5
323555665500	100	125	750	16.9	A21	CC8	33	5.0
323553871100	100	125	1000	15.5	A19	CC6	23	3.6
323556802800	100	125	2000	14.0	A19	CC6	23	2.5
323554942700	100	125	2500	14.2	A21	CC8	31	5.5
323555091000	100	125	5000	11.4	BR40	CC6	26	2.5
323551002100	100	130	750	15.9	A19	CC6	23	2.5
323558823600	100	130	1000	15.3	A19	CC6	23	3.6
323551164800	100	130	2500	14.0	A19	CC6	23	2.5
323556637700	100	130	2500	18.5	T4	CC8	23	4.0
323554560400	100	130	3500	13.4	A21	CC8	31	5.5
323554298400	100	140	1000	15.6	A60	CC6	26	2.0
323552902800	100	230	1000	10.5	A21	CC9	44	6.0
323557527200	100	230	3500	12.5	A60	CC9	34	3.4
323552832600	100	250	1000	11.7	A21	CC9	44	6.0
323552902900	100	277	1000	10.1	A21	CC9	44	6.0
323575582700	120	120	2000	12.8	BR40	CC6	28	4.0
323555181500	120	120	2000	10.6	BR40	CC6	24	2.5
323556712000	120	120	2000	15.5	T4	CC8	23	4.0



1560 Lisbon Street, Lewiston, Maine 04240
 Telephone: 207-333-6100 • Toll Free: 800-343-8008 (USA)
 www.elmettechnologies.com

Certified to ISO 9001 & 14001

Standard Coiled Coils for Incandescent Lamps

Part Number	Power Watts	Driver Volts	Life Hours	Design Lms/W	Lamp Type	Shape	Total Lgth [MM]	End Lgth [MM]
323555191400	120	120	2500	10.1	BR40	CC6	22	2.5
323555179100	120	125	2000	10.4	BR40	CC6	24	2.5
323555703800	120	125	5000	9.6	BR40	CC6	22	2.5
323555179000	120	130	2000	10.3	BR40	CC6	24	2.5
323556892100	120	130	2000	19.1	T4	CC8	23	4.0
323575589200	120	130	2000	12.5	BR40	CC6	28	4.0
323557505400	120	130	2000	11.5	ER40	CC6	24	5.3
323555665600	135	125	750	18.5	A21	CC8	33	5.0
323557520400	135	125	1000	17.1	A21	CC8	33	5.0
323555385800	135	125	2500	15.0	A21	CC8	33	5.0
323568904200	150	120	750	18.9	A21	CC8	32	5.0
320040002400	150	120	750	19.0	A21	CC8	32	4.8
323555386900	150	120	1000	19.0	A19	CC8	33	5.0
323556649500	150	120	2000	17.1	A23	CC8	33	5.0
323568965300	150	120	2000	11.8	R40	CC6	28	4.0
323556637900	150	120	2500	20.5	T4	CC8	23	4.0
323568905900	150	125	750	18.8	A21	CC8	32	5.0
323554943000	150	125	2500	16.3	A21	CC8	32	5.0
323578771300	150	130	750	18.9	A23	CC8	33	5.0
323555386400	150	130	2500	16.2	A21	CC8	33	5.0
323556643900	150	130	2500	20.2	T4	CC8	23	5.2
323557187900	150	220	1000	15.0	A21	CC9	38	3.0
323569022200	200	120	750	20.0	A23	CC8	33	5.0
323569025500	200	120	1000	19.2	T21	CC8	33	5.0
323556840300	200	120	1750	16.6	T21	CC8	32	5.0
323569023000	200	125	750	19.8	A23	CC8	33	5.0
323555651500	200	125	2500	17.3	A23	CC8	33	5.0
323569024800	200	130	750	19.7	A23	CC8	33	5.0
323550105600	200	130	2500	17.2	A23	CC8	33	5.0
323554259300	200	220	1000	15.8	PS25	CC9	44	3.0
323569173300	300	120	750	20.9	A25	CC8	37	5.0
323574883000	300	120	2500	18.0	PS25	CC8	37	5.0
323555651300	300	125	750	20.8	A25	CC8	37	5.0
323569175800	300	130	750	20.9	A25	CC8	37	5.0
323574884800	300	130	2500	17.7	A25	CC8	37	5.0
323574886300	500	130	2500	19.6	PS35	CC8	42	7.0